

MODEL FT1

Class I • 250°F or 350°F • 3 Hour • Galvanized Steel • Single Thickness Blade • Combination Fire/Smoke Damper

STANDARD MATERIALS AND CONSTRUCTION

- FRAME:** 5½" x 7⁄8" x 16-GA galvanized steel hat channel; Flat 16-GA galvanized head and sill for maximum free area on dampers ≤ 13" high
- BLADES:** 16-GA galvanized steel single thickness; Parallel action
- AXLES:** Plated solid steel stub
- BEARINGS:** Oil impregnated bronze
- LINKAGE:** Plated steel angle and crank plates with stainless steel pivots, in-jamb type or on-blade type
- STOPS:** 18-GA galvanized steel angles at head and sill
- BLADE SEALS:** Silicone
- JAMB SEALS:** Stainless steel
- SLEEVE:** Minimum 20-GA galvanized steel by 18" long (sizes greater than 84" wide or 84" high require minimum 18-GA)
- CAULKING:** Hardcast Irongrip 601 or UL-listed equivalent
- ACTUATOR:** Electric with heat response device (EHRD) or pneumatic with heat response device (PHRD); Factory-installed for Power-Open/Spring-Close (fail close) operation; External left hand mounted as viewed from jackshaft side of damper
- FINISH:** Mill

OPTIONS

- Exact Size
- Sleeve - Transition
- Actuators - 120V, 24V, 230V or Pneumatic
- Right Hand and/or Internal Actuator Mounting Locations (Restrictions Apply)
- Integral Dual Position Indication (IDPI) Switches
- Sensotherm Re-Openable Heat Response Device for Electric Actuator (ESOT)
- Sensotherm Re-Openable Heat Response Device for Pneumatic Actuator (SPOT)
- Model SM-501 Flow-Rated Smoke Detector (10" Minimum Damper Height)
- Model 2151 No-Flow Smoke Detector (12" Minimum Damper Height)
- Remote Test Box
- Copper Tubing (for Pneumatic Actuators)
- Transformers
- Tab-Lock Retaining Angles - 1 or 2 Sets
- Bearings - Stainless Steel
- Axle - Stainless Steel
- Security Bars
- Short-Width (<16") and/or Short-Height (<8") Transitions

NOTES

1. "A" width and "B" height are opening dimensions. Dampers are provided approximately ¼" undersize.
2. Damper with smoke detector must have a minimum sleeve of 19" (10.5" on the actuator side and 3" on the non-actuator side).
3. Dampers for horizontal installation can only be mounted in a fire barrier constructed of masonry/concrete materials.

DAMPER SIZES

		2000 fpm, 4 in.wg				3000 fpm, 4 in.wg		
Orientation	Hor & Vert	Horizontal		Vertical		Hor & Vert	Horizontal	Vertical
Panels	Minimum Panel	Max Panel	Max Assy	Max Panel	Max Assy	Max Panel 250°	Max Assy 250°	Max Assy 250°
Rectangular	4"W x 4"H (16"W x 8"H frame)	30"W x 48"H 36"W x 30"H	60"W x 48"H	36"W x 48"H 42"W x 36"H	108"W x 48"H	36"W x 36"H	60"W x 36"H	108"W x 36"H
Round	4" dia. (16"W x 8"H frame)	28" dia.	47" dia.	34" dia.	46" dia.	34" dia.	34" dia.	34" dia.
Oval	4"W x 4"H (16"W x 8"H frame)	28"W x 46"H 34"W x 28"H	58"W x 47"H	34"W x 46"H 40"W x 34"H	106"W x 46"H	34"W x 34"H	58"W x 34"H	106"W x 34"H


*Dampers smaller than minimum frame size require a transitions. Reference SD-TRFS.

UNDERWRITERS LABORATORIES INC.®
 CLASSIFIED DYNAMIC FIRE AND SMOKE DAMPER
 FIRE RESISTANCE RATING 3 HR
 LEAKAGE RESISTANCE CLASS I

air balance **FILE #R4708**

This combination fire/smoke damper meets the construction and performance requirements of:

- Underwriters Laboratories Inc. Standard 555S
- National Fire Protection Association Standards 80 and 90A
- ICC's International Building Code
- California State Fire Marshal Listing #3225-1328:115
- Underwriters Laboratories Inc. Approved for dual direction airflow and dynamic conditions.
- Underwriters Laboratories Inc. Classified for use in fire resistive ratings of 3 hours and longer
- Underwriters Laboratories Inc. Classified for use in smoke control systems for Leakage Class I and 250°F or 350°F.
- Actuators must be arranged to operate automatically, must fail closed upon loss of power, and must be controlled by a smoke detections system.



Dampers Louvers
 UL Life Safety Products
 Division of Mestek
 Member of AMCA

MODEL FT1

Class I • 250°F or 350°F • 3 Hour • Galvanized Steel • Single Thickness Blade • Combination Fire/Smoke Damper

Operations Rating:

Maximum Differential Pressure: 4 in.wg
 Maximum Face Velocity: 2000 fpm (3000 fpm for selected size/actuator combinations)

Leakage Rating:

UL Class I
 4 cfm per sq.ft. maximum @ 1 in.wg
 8 cfm per sq.ft. maximum @ 4 in.wg


Sound Ratings:

The Noise Criterion data below was tested in accordance with ASTM E477.99 in the center octave band.

Noise Criterion (NC)				
Damper Size	Velocity (fpm)			
	1000	2000	3000	4000
12"W x 12"H	31	53	64	71
24"W x 24"H	33	54	65	n/a

Pressure Drop Ratings:

The pressure drop data shown below is based on laboratory conditions. The test setup does not take into account elbows or other duct fittings that are part of every actual duct system. The configuration of the actual duct system immediately upstream and downstream of the damper often contributes more pressure loss than the damper itself.



This product was tested in accordance with AMCA Standard 500D.



Dampers Louvers
 UL Life Safety Products
 Division of Mestek
 Member of AMCA